

Key Engine Specifications

Manufacturer/Model Kohler ECH749, EFI, 2 cyl Displacement 747CC (45.6 cu. in.)

Horsepower/RPM 29 @ 3600 Max Torque (ft-lbs) 44.3 @ 2400

Fuel Gasoline (unleaded - Min. 87 Octane)
Fuel Capacity (U.S. Gal)
9.4 (35.6 liter)

Fuel Consumption (per Hr.)Cooling System

Lubrication System Full Pressure w/ Filter

Quick Reference Dimensions

<u>Tractor</u> <u>Weight</u>* <u>Overall Dimensions</u> Tractor 750

Tractor & Deck° 1195 46-1/4 H x 64[^] W x 107 L

* Approximate pounds Dimensions and weight shown for models equipped with 60" deck (typical)

1.17 gallon (4.43 liter)

^ 60" deck with side discharge shield folded

Popular Options

- Headlights
 All-Trail Drive Tires
- Roll Over Protection Structure (ROPS)

Compatible Decks

 Dedicated 52" Rear Discharge/Mulch or 60" Side Discharge deck with Tilt-Up function [Deck Arm Adapter Kit (P/N 2430-10) available for using other Walker decks on Model MBS]

Compatible Implements/Attachments

- · Implement Hitch
- Two-Stage Snowblower (50")
- Dozer Blade (60")
- Rotary Broom (47")



walkermowers.com

WALKER OWERS

out front mowing

Model MBV



Model MBV

The MBV is a simple, clean design using many of the same principles as the Walker original, and it includes a powerful Briggs & Stratton Vanguard engine and simplified drive train. It is specifically designed to side discharge or mulch using gear-driven decks up to 56".

• 18-hp Briggs & Stratton Vanguard, twin-cylinder, 570 cc engine

• Two independent Hydro-Gear® ZT3100 transaxles combine to make an agile tractor (top speed of 8 mph)

Remote Cummins Filtration OptiAir™ engine air filter for increased engine life

• Belt tightener clutch/band brake for mower deck and implement drive

- Tilt-up body completely exposes drive train
- Full size garden tractor battery
- 2.8-gallon fuel tank
- Parking brake

Key Engine Specifications

Manufacturer/Model Briggs & Stratton Vanguard, 2 cyl.

570 cc (34.7 cu. in.) Displacement Horsepower/RPM 18 @ 3600 29.5 @ 2400 Max Torque (ft-lbs)

Gasoline (unleaded - min. 87 octane)

 Fuel Capacity (U.S. gal) 2.8 (10.6 liter) Fuel Consumption (Per hour) 1.06 gallon (4.01 liter)

Cooling System

Full Pressure w/ Filter · Lubrication System

Quick Reference Dimensions

Tractor Weight' **Overall Dimensions**

Tractor 562

Tractor & Deck° 40-1/2 H x 44[^] W x 82 L

Popular Options

- Comfort Seat
- Armrests
- Narrow Drive Tires All-Terrain Drive Tires
- · Mechanical Deck Lift · Headlights
- Low-Profile Drive Tires (10.5)

Compatible Decks

- Side Discharge (SD) 36", 42", 48", 56"
- Mulching (ML) 36", 42", 48"

Note: Based on horsepower, the DML48 on this model may deliver marginal results in some conditions

Compatible Implements/Attachments

• Single-Stage Snowblower (36") - Requires Kit (P/N 4300-16)



* Approximate pounds ° Dimensions and weight shown for models equipped with 42" deck (typical)

^ 42" deck with discharge shield folded



Key Engine Specifications

Manufacturer/Model Yanmar 3TNM72, 3 cyl.
Displacement 904 cc (55.17 cu. in.)

Horsepower (Net Rated) 23.6 Max Torque (ft-lbs) 40.9 @ 2600

Fuel Diesel (2-D)
Fuel Capacity (U.S. gal)
9.4 (36 liter)

Fuel Consumption (per hour) .95 gallon (3.59 liter)

Cooling System Liqu

Lubrication System
 Full Pressure w/ Filter

Quick Reference Dimensions

<u>Tractor</u> <u>Weight</u>* <u>Overall Dimensions</u> Tractor 927

Tractor & Deck° 1372 46-1/4 H x 64^ W x 107 L
*Approximate pounds ° Dimensions and weight shown for models equipped with 60" deck (typical)

^ 60" deck with side discharge shield folded

Popular Options

- Headlights
 All-Trail Drive Tires
- Roll Over Protection Structure (ROPS)

Compatible Decks

 Dedicated 52" Rear Discharge/Mulch or 60" Side Discharge deck with Tilt-Up function [Deck Arm Adapter Kit (P/N 2430-10) available for using other Walker decks on Model MBS]

Compatible Implements/Attachments

- Implement Hitch
- Two-Stage Snowblower (50")
- Dozer Blade (60")
- Rotary Broom (47")

